Serial No.: 09/692,869 Filed: October 20, 2000

Page : 2 of 9

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

seal.

1. (Currently Amended) A battery <u>system</u>, comprising:

<u>a casing configured to receive one or more batteries and to be used with an electronic device; and</u>

a battery comprising

a can having a rectangular cross section, the can having a closed end and an open end;

a cathode in the can;

an anode in the can;

a separator between the cathode and the anode; and

a seal assembly attached to the open end of the can,

wherein the seal assembly comprises a seal and a current collector attached to the

- 2. (Currently Amended) The battery <u>system</u> of claim 1, wherein the can comprises an air access opening.
- 3. (Currently Amended) The battery <u>system</u> of claim 1, wherein the cathode comprises manganese oxide.
- 4. (Currently Amended) The battery <u>system</u> of claim 1, wherein the cathode has a rectangular cross section.
- 5. (Currently Amended) The battery <u>system</u> of claim 1, wherein the anode comprises zinc.
 - 6. (Canceled)
- 7. (Currently Amended) The battery <u>system</u> of claim 1, wherein the battery is a metal-air battery.
 - 8. (Currently Amended) The battery of claim 1, A battery, comprising: a can having a rectangular cross section, the can having a closed end and an open end;

Serial No.: 09/692,869 Filed: October 20, 2000

Page : 3 of 9

a cathode in the can;

further comprising a conductive hot melt material between the cathode and the can; an anode in the can;

a separator between the cathode and the anode; and

a seal assembly attached to the open end of the can,

wherein the seal assembly comprises a seal and a current collector attached to the seal.

9. (Previously Presented) A battery, comprising:

a can having a rectangular cross section, the can having a closed end and an open end; a cathode in the can;

an anode in the can;

a separator between the cathode and the anode;

a seal assembly attached to the open end of the can; and

a non-conductive melt between the cathode and the seal assembly.

- 10. (Original) The battery of claim 1, further comprising a barrier layer between the cathode and the can.
- 11. (Original) The battery of claim 10, wherein the barrier layer comprises polytetrafluoroethylene.
- 12. (Original) The battery of claim 1, wherein the cathode and the can define an air plenum therebetween.
 - 13. (Original) The battery of claim 1, wherein the can has a square cross section.
 - 14. (Canceled)
- 15. (Currently Amended) The method of claim 14, A method of making a metal-air battery, the method comprising:

placing a cathode tube in a can having a rectangular cross section and an air access opening;

placing an anode in the can;

placing a seal assembly in the can;

sealing a portion of the can over the seal assembly; and

further comprising placing a conductive melt in the can.

- 16. (Canceled)
- 17. (Canceled)

Serial No.: 09/692,869 Filed: October 20, 2000

Page : 4 of 9

18. (Previously Presented) A method of making a metal-air battery, the method comprising:

placing a cathode tube in a can having a rectangular cross section and an air access opening;

placing an anode in the can;
placing a seal assembly in the can;

sealing a portion of the can over the seal assembly; and placing a non-conductive melt between the cathode and the seal assembly.

- 19. (Canceled)
- 20. (Canceled)
- 21. (Previously Presented) A battery, comprising:
- a can having a triangular cross section, the can having a closed end and an open end;

a cathode in the can;

an anode in the can;

a separator between the cathode and the anode; and

a seal assembly attached to the open end of the can,

wherein the seal assembly comprises a seal and a current collector attached to the seal.

- 22. (Original) The battery of claim 21, wherein the can comprises an air access opening.
- 23. (Original) The battery of claim 21, wherein the cathode comprises manganese oxide.
- 24. (Original) The battery of claim 21, wherein the cathode has a triangular cross section.
 - 25. (Original) The battery of claim 21, wherein the battery is a metal-air battery.
- 26. (Original) A method of making a metal-air battery, the method comprising: placing a cathode tube in a can having a triangular cross section and an air access opening;

placing an anode in the can; placing a seal assembly in the can; and sealing a portion of the can over the seal assembly.

27. (Currently Amended) A battery <u>system</u>, comprising:

<u>a casing configured to receive one or more batteries and to be used with an electronic device;</u> and

Serial No.: 09/692,869 Filed: October 20, 2000

Page : 5 of 9

a battery comprising

a can having a polygonal cross section, the can having a closed end and an open end;

a cathode in the can, the cathode defining a cavity; an anode in the cavity; and a separator between the cathode and the anode.

- 28. (Currently Amended) The battery <u>system</u> of claim 27, wherein the can has a rectangular cross section.
- 29. (Currently Amended) The battery <u>system</u> of claim 27, wherein the can has a square cross section.
 - 30. (Currently Amended) The battery of claim 27, A battery, comprising: a can having a polygonal cross section, the can having a closed end and an open end, a cathode in the can, the cathode defining a cavity, an anode in the cavity, and a separator between the cathode and the anode, wherein the can has a triangular cross section.
- 31. (Currently Amended) The battery <u>system</u> of claim 27, wherein the can has a wall between the closed end and the open end, the wall having an air access opening.
- 32. (Currently Amended) The battery <u>system</u> of claim 27, wherein the can is electrically conductive.
- 33. (Currently Amended) A battery <u>system</u>, comprising:
 <u>a casing configured to receive one or more batteries and to be used with an electronic device; and</u>

a battery comprising

a can having a polygonal cross section, the can having a closed end, an open end, and a wall extending between the ends, the wall having an air access opening;

a cathode in the can;

an anode in the cavity;, and

a separator between the cathode and the anode.

- 34. (Currently Amended) The battery <u>system</u> of claim 33, wherein the can has a rectangular cross section.
- 35. (Currently Amended) The battery <u>system</u> of claim 33, wherein the can has a square cross section.

Serial No.: 09/692,869 Filed: October 20, 2000

Page : 6 of 9

36. (Currently Amended) The battery of claim 33, A battery, comprising:

a can having a polygonal cross section, the can having a closed end, an open end, and a wall extending between the ends, the wall having an air access opening,

a cathode in the can,

an anode in the cavity, and

a separator between the cathode and the anode,

wherein the can has a triangular cross section.

37. (Currently Amended) A battery <u>system</u>, comprising:

a casing configured to receive one or more batteries and to be used with an electronic device; and

a battery comprising

a can having a polygonal cross section, the can having a closed end, an open end, and two walls extending between the ends, the distance between the ends being greater than the distance between the walls;

a cathode in the can;

an anode in the cavity;, and

a separator between the cathode and the anode.

- 38. (Currently Amended) The battery <u>system</u> of claim 37, wherein at least one wall has an air access opening.
- 39. (Currently Amended) The battery <u>system</u> of claim 37, wherein the cathode defines a cavity, and the anode is in the cavity.
- 40. (Currently Amended) The battery <u>system</u> of claim 37, wherein the can is electrically conductive.
- 41. (Currently Amended) The battery <u>system</u> of claim 37, wherein the can has a rectangular cross section.
- 42. (Currently Amended) The battery <u>system</u> of claim 37, wherein the can has a square cross section.
 - 43. (Currently Amended) The battery of claim 37, A battery, comprising:

a can having a polygonal cross section, the can having a closed end, an open end, and two walls extending between the ends, the distance between the ends being greater than the distance between the walls;

a cathode in the can;

an anode in the cavity; and

a separator between the cathode and the anode,

wherein the can has a triangular cross section.

Applicant: William McHugh, et al.

Serial No.: 09/692,869 Filed: October 20, 2000

Page : 7 of 9

44. (Currently Amended) The battery <u>system</u> of claim 37, further comprising a seal assembly attached to the open end, the seal assembly including a seal and a current collector.

Attorney's Docket No.: 08935-218001 / M-4926